



«Prime-C» LLP  
 BIN 170940000095  
 100000, Republic of Kazakhstan, Karaganda, Erzhanova 18, BC «Respect», off. №817  
 IIC KZ06914052203KZ002W3 in "Sberbank" SB JSC  
 Phone: +7(7212)910-116; Mob.: +7(701)806-75-06, +7(775)700-30-30  
 e-mail: info@prime-c.kz

## OBV – Raiser Dialectic Rods Buffer



### Application

Distribution cable for indoor installation with direct access to fibers.

### Technical characteristics

Parameter	Value				
Number of optical fibers	Up to 4	Up to 12	Up to 24	Up to 36	Up to 48
Tensile strength, kN	400				
Cable diameter, mm	6,5	8,5	10,5	14,5	14,5
Cable weight, kg/km	41,5	63,8	90,1	156,5	168,6
Bending radius, mm	65	85	105	145	145
Crushing force, kN/sm	80				
Operating temperature	-30°C...+50°C				
Installation temperature	-10°C...+50°C				
Transportation and storage temperature	-50°C...+50°C				
Minimum bending radius	Not less than 10 cable diameters				
Factory length, km	4				

### Technical characteristics of optical fiber

Type of optical fiber	Corning SMF 28 Ultra	Corning SMF28e+BB
ITU-T recommendations	G.657A1 G.652D	G.657A1 G.652D
Deviation from the concentricity of the core, microns, not more	0,5	
Diameter of fiber sheath, microns	125±0,7	
Deviation from the roundness of the sheath,%, not more	0,7	
The diameter of the protective covering, microns	242±5	
Maximum attenuation at wavelength 1310 nm	0,32	0,34
Maximum attenuation at wavelength 1550 nm	0,18	0,20

### Full name example

#### Optical cable OBV-ng(A)-HF-24Y (3x8) 400N

The cable consists of bundle of optical fibers in a buffer. The cable sheath is flame retardant, with low smoke and gas emission, does not emit corrosive and gaseous products during combustion and decay, with low toxicity of combustion gases. In the cable sheath, two fiberglass rods are diametrically laid, which prevent axial torsion of the cable and perform the functions of strength elements.