



«Prime-C»LLP
 BIN 170940000095
 100000, Republic of Kazakhstan, Karaganda, 18 Erzhanov str., BC «Respect», office 817
 IICKZ06914052203KZ002W3 in SB "Sberbank» JSC
 Phone: +7(7212)910-116; Mob.:+7(701)806-75-06, +7(775)700-30-30
 e-mail: info@prime-c.kz

OKKTS – In Duct Single Tube



- 1. PE outer sheath*
- 2. Corrugated steel armor
- 3. Hydrophobic gel
- 4. Buffer tube
- 5. Hydrophobic gel
- 6. Optical fiber

* It is possible to produce a cable with flame-redundant outer sheath, with low smoke and gas emission (ng(A)-HF)

Application

Optical cable is designed for installation in cable ducts, in trays, in blocks, in tunnels, in collectors, in headers, on bridges and skyways, between and inside buildings in case of damage probability by rodents.

Technical characteristics

Parameter	Value		
Tensile strength, kN	2,7		
Number of optical fibers	2-12	16	24
Cable diameter, mm	7,3	7,5	7,8
Cable weight, kg/km	68,9	70,8	73,8
Crushing force, kN/sm	0,5		
Operating temperature	-50°C...+70°C		
Installation temperature	-30°C...+50°C		
Transportation and storage temperature	-50°C...+70°C		
Minimum bending radius	Not less than 15 cable diameters		
Factory length, km	4 km		

Technical characteristics of optical fiber

Type of optical fiber	Corning SMF 28 Ultra	Corning SMF28e+BB
ITU-T recommendations	G.657A1 G.652D	G.657A1 G.652D
Deviation from the concentricity of the core, microns, not more	0,5	
Diameter of fiber sheath, microns	125±0,7	
Deviation from the roundness of the sheath,%, not more	0,7	
The diameter of the protective covering, microns	242±5	
Maximum attenuation at wavelength 1310 nm	0,32	0,34
Maximum attenuation at wavelength 1550 nm	0,18	0,20

Full name example

Optical cable OKKTS-08G.652D 2,7kN

The optical cable for duct installation consist of a single tube core with freely laid fibers of G.652D Standard, the maximum tensile force is 2,7 kN.