

«Prime-C»LLP BIN 170940000095

100000, Republic of Kazakhstan, Karaganda, 18 Erzhanov str., BC «Respect», office 817

IIC KZ06914052203KZ002W3 in SB "Sberbank» JSC

Phone: +7(7212)910-116; Mob.:+7(701)806-75-06, +7(775)700-30-30

e-mail: info@prime-c.kz

Adapter SC/UPC SM flanged



The adapter is designed for connecting SC-type optical connectors with straight spherical (UPC) polishing of single-mode (SM) fiber.

The body frame made of blue plastic. The tips of optical connectors are joined using a precision centering sleeve made of zirconium ceramics. The connectors are secured with hidden latches. On the connecting parts of the adapter housing there are recesses for the key plugs of the connectors. The socket is attached to the adapter bar using a metal stopper. The socket body also has flanges with 2 mm diameter holes for mounting.

Technical characteristics

Manufacturer	СВЯЗЬСТРОЙДЕТСИЬ
Body frame material	Plastic
Centering sleeve material	Ceramics
Storage temperature, °C	-40 +80
Operation temperature, °C	-20 +70
Dimensions, mm	15x9,4x27,4
Weight, g	4,8

Complete set

Adapter, pc	1
Protective plug, pc	2