



«Prime-C» LLP
BIN 170940000095
100000, Republic of Kazakhstan, Karaganda, 18 Erzhanov str., BC «Respect», office 817
IIC KZ06914052203KZ002W3 in SB "Sberbank» JSC
Phone: +7(7212)910-116; Mob.:+7(701)806-75-06, +7(775)700-30-30
e-mail: info@prime-c.kz


Optical closure MCO-P1



The outdoor fiber dome closure MCO-P1/A is designed for installation of an overhead trunk cable with subscriber drops of self-supporting small sized drop cables. The feature of all MCO distribution boxes with the letter 'A' is a plate or sockets for installation of adapters inside it. This allows to use terminated subscriber drop cables and enables cross connect.

It is a small-sized sealed rectangular container. A detachable mounting insert is installed inside the container, two splice holders are placed on the backside and the jacks for installation of SC type adapters are located on the front side of the panel. A splitter holder is on the front part of the panel there is possible to install the splitters in mini-body frames with fibers of length 1 m with 900 µm buffer.

Technical characteristics

Manufacturer	
Number of ports	10
Type of adapters	At the request of the customer
Max. number of splices	36
Number of entered FOC: - up to 9 mm / transit - oval - up to 5 mm	2/1 8
Max. number of trays	2
Method of sealing the case and entered FOC	Mechanical
Sealing method	Elastomer
Operating temperature, °C	- 60...+70