



«Prime-C» LLP
 BIN 170940000095
 100000, Republic of Kazakhstan, Karaganda, Erzhanova 18, BC «Respect», off. №817
 IIC KZ06914052203KZ002W3 in "Sberbank" SB JSC
 Phone: +7(7212)910-116; Mob.: +7(701)806-75-06, +7(775)700-30-30
 e-mail: info@prime-c.kz

TOL – In Duct Single Tube



- 1. Outer sheath
- 2. Steel wire
- 3. Corrugated steel tape armor
- 5. Loose tube
- 6. Hydrophobic gel
- 7. Optical fiber

* It is possible to produce a cable with flame redundant outer sheath, with low smoke and gas emission (ng(A)-HF)

Application

Optical cable is designed for installation in cable ducts, in pipes, in blocks, in trays, in tunnels, in headers, on bridges and skyways, between and inside buildings.

Technical characteristics

Parameter	Value		
	Up to 12	Up to 16	Up to 24
Number of optical fibers	Up to 12	Up to 16	Up to 24
Tensile strength, kN	2,7		
Cable diameter, mm	7,3	7,5	7,8
Cable weight, kg/km	70,5	72,6	75,7
Bending radius, mm	109,5	112,5	117,0
Crushing force, kN/sm	0,5		
Operating temperature	-50°C...+70°C		
Installation temperature	-30°C...+50°C		
Transportation and storage temperature	-60°C...+70°C		
Minimum bending radius	Not less than 15 cable diameters		
Factory length, km	4		

Technical characteristics of optical fiber

Type of optical fiber	Corning SMF 28 Ultra	Corning SMF28e+BB
ITU-T recommendations	G.657A1 G.652D	G.657A1 G.652D
Deviation from the concentricity of the core, microns, not more	0,5	
Diameter of fiber sheath, microns	125±0,7	
Deviation from the roundness of the sheath,%, not more	0,7	
The diameter of the protective covering, microns	242±5	
Maximum attenuation at wavelength 1310 nm	0,32	0,34
Maximum attenuation at wavelength 1550 nm	0,18	0,20

Full name example

Optical cable TOL-P-24Y (1x24) 2.7kN

The cable consists of a single tube core with freely laid fibers are twisted. The free space is filled with a hydrophobic gel in the optical loose tubes and in the core. The core is covered with corrugated steel tape armor and a flame redundant while single installation sheath. Two fiberglass rods are diametrically laid, which perform the functions of strength elements.